

SC-7400

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Issue date: 12/11/2021 Revision date: 07/07/2022 Supersedes version of: 12/11/2021 Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : SC-7400
Product code : P07400
Type of product : Selfshine cream.

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Hand application on shoe.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

ABC Leather, S.L.
Pol. Ind. Les Comes - C/França, 14.
P.O. Box 08700
08700 Igualada - España
T + 34 93 803 96 35 - F +34 93 804 71 75
abcleather@abcleather.es - www.ABCleather.es

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225
Serious eye damage/eye irritation, Category 2 H319
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) :

Danger

Hazard statements (CLP) :

H225 - Highly flammable liquid and vapour.

H319 - Causes serious eye irritation.

SC-7400

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Issue date: 12/11/2021 Revision date: 07/07/2022 Supersedes version of: 12/11/2021 Version: 1.1

Precautionary statements (CLP)	<ul style="list-style-type: none"> : P280 - Wear protective gloves, eye protection. P210 - Keep away from heat, hot surfaces, open flames, sparks. No smoking. P241 - Use explosion-proof electrical, ventilating, lighting equipment. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention. P370+P378 - In case of fire: Use extinguishing powder, foam, carbon dioxide (CO₂), Water spray to extinguish. P235 - Keep cool. P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	<ul style="list-style-type: none"> : EUH208 - Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one. May produce an allergic reaction.

2.3. Other hazards

Other hazards which do not result in classification : None known.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
propan-2-ol	(CAS-No.) 67-63-0 (EC-No.) 200-661-7 (EC Index-No.) 603-117-00-0 (REACH-no) 01-2119557558-25	≥ 15 - < 20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
ethanol; ethyl alcohol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5 (REACH-no) 01-2119457610-43	≥ 7 - ≤ 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319
Alcohols, C11-C15 secondary ethoxylated.	(CAS-No.) 68131-40-8 (EC-No.) 614-295-4	≥ 2 - < 3	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 3, H412
Ammonia	(CAS-No.) 1336-21-6 (EC-No.) 215-647-6 (EC Index-No.) 007-001-01-2 (REACH-no) 01-2119488876-14	≥ 0.2 - < 1	Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400

SC-7400

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Issue date: 12/11/2021 Revision date: 07/07/2022 Supersedes version of: 12/11/2021 Version: 1.1

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
Ammonia	(CAS-No.) 1336-21-6 (EC-No.) 215-647-6 (EC Index-No.) 007-001-01-2 (REACH-no) 01-2119488876-14	(5 ≤ C ≤ 100) STOT SE 3, H335

Comments : There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.
See Section 8 for information on personal protection equipment

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Give oxygen or artificial respiration if necessary. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical advice/attention if you feel unwell. If unconscious, place in the recovery position and seek medical advice. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

First-aid measures after skin contact : Wash skin with plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Get medical attention if symptoms occur. Thoroughly clean shoes before re-using.

First-aid measures after eye contact : Immediately rinse with water for a prolonged period while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. Continue to rinse for at least 10 minutes. Get medical attention.

First-aid measures after ingestion : Rinse mouth thoroughly with water. Remove dentures if any. Remove person to fresh air and keep comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do NOT induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Call a poison center or a doctor if you feel unwell. Never give anything by mouth to an unconscious person. If unconscious, place in the recovery position and seek medical advice. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Causes serious eye irritation.

Symptoms/effects after inhalation : No specific data.

Symptoms/effects after skin contact : No specific data.

Symptoms/effects after eye contact : Causes serious eye irritation. Exposed may experience eye tearing, redness and discomfort.

Symptoms/effects after ingestion : No specific data.

SC-7400

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
 Issue date: 12/11/2021 Revision date: 07/07/2022 Supersedes version of: 12/11/2021 Version: 1.1

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. No specific treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : dry chemical powder. carbon dioxide. Water spray. Foam.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : In a fire or if heated, a pressure increase will occur and the container may burst.

Explosion hazard : Prevent the product from entering drains (risk of explosion).

Hazardous decomposition products in case of fire : Thermal decomposition generates : carbon dioxide. carbon monoxide. nitrogen oxides.

5.3. Advice for firefighters

Precautionary measures fire : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if it can be done without personal risk. Use water spray or fog for cooling exposed containers.

Protection during firefighting : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 provides a basic level of protection in case of chemical incident.

Other information : No additional information available.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No action shall be taken involving any personal risk or without suitable training. Evacuate area.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate area. Evacuate unnecessary personnel. Only qualified personnel equipped with suitable protective equipment may intervene. Do not touch or walk on the spilled product. Do not breathe vapours. Maintain an open airway. In case of inadequate ventilation wear respiratory protection. Wear personal protective equipment.

6.1.2. For emergency responders

Protective equipment : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2. Environmental precautions

Avoid the dispersion of spilled material, its contact with the ground, waterways, drainage pipes and sewers. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak without risks if possible. Move containers from fire area if it can be done without personal risk. Use non-sparking tools.



SC-7400

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Issue date: 12/11/2021 Revision date: 07/07/2022 Supersedes version of: 12/11/2021 Version: 1.1

- Methods for cleaning up : Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill: Stop leak if without risk. Move containers from spill area.
Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows.
Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Dispose of via a licensed waste disposal contractor.
- Other information : Contaminated absorbent material may pose the same hazard as the spilled product.

6.4. Reference to other sections

See Heading 1 for emergency contact information. For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13: additional waste treatment information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Use personal protective equipment as required. For further information refer to section 8: "Exposure controls/personal protection". Do not ingest. Do not get in eyes, on skin, or on clothing. Avoid breathing vapours, mist. Use only outdoors or in a well-ventilated area. In case of insufficient ventilation, wear suitable respiratory equipment. Do not enter in closed warehouse without respirator or without assurance of sufficient oxygen presence. Keep container tightly closed. Keep in original containers. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Flame proof, lighting, electrical equipment and ventilation. Use only non-sparking tools. Take precautionary measures against static discharge. Empty containers retain product residue and can be hazardous. Do not re-use empty containers.
- Hygiene measures : Do not eat, drink or smoke in areas where product is used. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Remove contaminated clothing and protective equipment before entering eating areas. For further information refer to section 8: "Exposure controls/personal protection".

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations.
- Storage conditions : Store in accordance with local regulations. Store separately. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate ignition sources. Separate from oxidizing materials. Keep container closed when not in use. Opened containers must be carefully closed and kept upright to avoid leakage. Do not store in unlabeled containers. Use appropriate container to avoid environmental contamination. Protect from low temperatures. Stir product before use.
- Incompatible materials : Oxidizing materials.

7.3. Specific end use(s)

No additional information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

propan-2-ol (67-63-0)	
United Kingdom - Occupational Exposure Limits	
Local name	Propan-2-ol

SC-7400

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
 Issue date: 12/11/2021 Revision date: 07/07/2022 Supersedes version of: 12/11/2021 Version: 1.1

propan-2-ol (67-63-0)	
WEL TWA (OEL TWA) [1]	999 mg/m ³
WEL TWA (OEL TWA) [2]	400 ppm
WEL STEL (OEL STEL)	1250 mg/m ³
WEL STEL (OEL STEL) [ppm]	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

ethanol; ethyl alcohol (64-17-5)	
United Kingdom - Occupational Exposure Limits	
Local name	Ethanol
WEL TWA (OEL TWA) [1]	1920 mg/m ³
WEL TWA (OEL TWA) [2]	1000 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Monitoring methods	
Monitoring methods	If this product contains ingredients with exposure limits, personal, work or biological monitoring may be necessary to determine the effectiveness of ventilation or other control measures and / or the need to wear respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

8.2. Exposure controls

Appropriate engineering controls:

Use only in well ventilated areas. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Flame proof, lighting, electrical equipment and ventilation.

Personal protective equipment:

Safety glasses. Gloves. Protective clothing.

Materials for protective clothing:
Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Hand protection:
Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

SC-7400

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Issue date: 12/11/2021 Revision date: 07/07/2022 Supersedes version of: 12/11/2021 Version: 1.1

Eye protection:

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Wear security glasses which protect from splashes

Skin and body protection:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Respiratory protection:

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Personal protective equipment symbol(s):



Environmental exposure controls:

Emissions from ventilation equipment or work processes should be verified to ensure that they meet the requirements of environmental protection legislation. In some cases it will be necessary to use smoke scrubbers, filters or modify the design of the process equipment to reduce emissions to an acceptable level.

Other information:

Wash your hands, forearms and face thoroughly after handling chemicals, before eating, smoking and using the bathroom and at the end of the day. Appropriate techniques should be used to remove potentially contaminated clothing. Take off immediately all contaminated clothing and wash it before reuse. Verify that eyewash stations and safety showers are close to the workstation location.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Paste.
Colour	: Beige.
Odour	: Solvent.
Odour threshold	: No data available
pH	: 8,5 – 10
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 78 °C
Flash point	: 22 °C Closed cup
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 0,99 @20°C
Solubility	: Miscible with water.
Partition coefficient n-octanol/water (Log Pow)	: No data available

SC-7400

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Issue date: 12/11/2021 Revision date: 07/07/2022 Supersedes version of: 12/11/2021 Version: 1.1

Viscosity, kinematic	: No data available
Viscosity, dynamic	: 100000 – 200000 mPa.s
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 25,9 % Definition according to EU Directive 2004/42/EC: All organic compounds with a boilingpoint of <= 250 °C at 101,3 kPa.
Other properties	: No supplementary information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Not considered to be reactive according to our database.

10.2. Chemical stability

The product is stable.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5. Incompatible materials

Oxidizing materials.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Decomposition products may be a hazard to health. Serious effects may be delayed following exposure.
Additional information	: No known significant effects or critical hazards.

SC-7400

ATE CLP (oral)	18713,4 mg/kg
ATE CLP (dust,mist)	56,1 mg/l

propan-2-ol (67-63-0)

LD50 oral rat	5840 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	12800 mg/kg
ATE CLP (oral)	5840 mg/kg bodyweight
ATE CLP (dermal)	12800 mg/kg bodyweight

SC-7400

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
 Issue date: 12/11/2021 Revision date: 07/07/2022 Supersedes version of: 12/11/2021 Version: 1.1

ethanol; ethyl alcohol (64-17-5)	
LD50 oral rat	15010 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 14450 - 15560
LD50 oral	8300 mg/kg bodyweight Animal: mouse, Remarks on results: other:
LC50 Inhalation - Rat (Vapours)	124,7 mg/l/4h

Alcohols, C11-C15 secondary ethoxylated. (68131-40-8)	
LD50 oral rat	≥ 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), Guideline: EU Method B.1 tris (Acute Oral Toxicity - Acute Toxic Class Method), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity), Guideline: other:
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LD50 dermal rabbit	11000 mg/kg
ATE CLP (oral)	500 mg/kg bodyweight
ATE CLP (gases)	4500 ppmv/4h
ATE CLP (vapours)	11 mg/l/4h
ATE CLP (dust,mist)	1,5 mg/l/4h

Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: 8,5 – 10
Serious eye damage/irritation	: Causes serious eye irritation. Exposed may experience eye tearing, redness and discomfort. pH: 8,5 – 10
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (No known significant effects or critical hazards.)
Carcinogenicity	: Not classified (No known significant effects or critical hazards.)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: Not classified (Not available)
STOT-repeated exposure	: Not classified (Not available)

ethanol; ethyl alcohol (64-17-5)	
LOAEL (oral, rat, 90 days)	3200 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	1730 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Remarks on results: other:
NOAEL (subchronic, oral, animal/male, 90 days)	< 9700 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
NOAEL (subchronic, oral, animal/female, 90 days)	> 9400 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)

Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Potential adverse human health effects and symptoms	: Causes serious eye irritation. Decomposition products may be a hazard to health. Serious effects may be delayed following exposure.

SC-7400

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Issue date: 12/11/2021 Revision date: 07/07/2022 Supersedes version of: 12/11/2021 Version: 1.1

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Not available.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

propan-2-ol (67-63-0)

LC50 - Fish [1]	10000 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	9640 mg/l Test organisms (species): Pimephales promelas

ethanol; ethyl alcohol (64-17-5)

LC50 - Fish [1]	14,2 g/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	1074 mg/l Fresh water
EC50 72h - Algae [1]	50 mg/l Marine water
EC50 96h - Algae [1]	≈ 22000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	9,6 mg/l Test organisms (species): Daphnia magna Duration: '9 d'
NOEC chronic crustacea	100 mg/l Fresh water - Daphnia
NOEC chronic algae	50 mg/l Marine water

Alcohols, C11-C15 secondary ethoxylated. (68131-40-8)

NOEC (chronic)	0,2 mg/l Test organisms (species): Duration: '21 d'
----------------	---

12.2. Persistence and degradability

SC-7400

Persistence and degradability	Not established.
-------------------------------	------------------

12.3. Bioaccumulative potential

SC-7400

Bioaccumulative potential	Not established.
---------------------------	------------------

propan-2-ol (67-63-0)

Partition coefficient n-octanol/water (Log Pow)	0,05
Bioaccumulative potential	Low.

ethanol; ethyl alcohol (64-17-5)

Partition coefficient n-octanol/water (Log Pow)	-0,35
Bioaccumulative potential	Low.



SC-7400

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Issue date: 12/11/2021 Revision date: 07/07/2022 Supersedes version of: 12/11/2021 Version: 1.1

Alcohols, C11-C15 secondary ethoxylated. (68131-40-8)	
Partition coefficient n-octanol/water (Log Pow)	5,9
Bioaccumulative potential	High.

12.4. Mobility in soil

SC-7400	
Ecology - soil	No additional information available.

12.5. Results of PBT and vPvB assessment

SC-7400	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

12.6. Other adverse effects

Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Product/Packaging disposal recommendations	: Eliminate or minimize waste generation when possible. Residual containers must be recycled. Recycling is preferred to disposal or incineration.
Additional information	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers.
Ecology - waste materials	: The classification of the product may meet the criteria for a hazardous waste.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number

UN-No. (ADR)	: UN 1263
UN-No. (IMDG)	: UN 1263
UN-No. (IATA)	: UN 1263
UN-No. (ADN)	: UN 1263
UN-No. (RID)	: UN 1263

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: PAINT RELATED MATERIAL
Proper Shipping Name (IMDG)	: PAINT RELATED MATERIAL
Proper Shipping Name (IATA)	: Paint related material
Proper Shipping Name (ADN)	: PAINT RELATED MATERIAL

SC-7400

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
 Issue date: 12/11/2021 Revision date: 07/07/2022 Supersedes version of: 12/11/2021 Version: 1.1

Proper Shipping Name (RID) : PAINT RELATED MATERIAL
 Transport document description (ADR) : UN 1263 PAINT RELATED MATERIAL, 3, II, (D/E)
 Transport document description (IMDG) : UN 1263 PAINT RELATED MATERIAL, 3, II
 Transport document description (IATA) : UN 1263 Paint related material, 3, II
 Transport document description (ADN) : UN 1263 PAINT RELATED MATERIAL, 3, II
 Transport document description (RID) : UN 1263 PAINT RELATED MATERIAL, 3, II

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 3
 Danger labels (ADR) : 3



IMDG

Transport hazard class(es) (IMDG) : 3
 Danger labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
 Danger labels (IATA) : 3



ADN

Transport hazard class(es) (ADN) : 3
 Danger labels (ADN) : 3



RID

Transport hazard class(es) (RID) : 3
 Danger labels (RID) : 3



14.4. Packing group

Packing group (ADR) : II
 Packing group (IMDG) : II
 Packing group (IATA) : II

SC-7400

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
 Issue date: 12/11/2021 Revision date: 07/07/2022 Supersedes version of: 12/11/2021 Version: 1.1

Packing group (ADN) : II
 Packing group (RID) : II

14.5. Environmental hazards

Dangerous for the environment : No
 Marine pollutant : No
 Other information : No supplementary information available

14.6. Special precautions for user

Special transport precautions : Transportation within the users' facilities: always transport in closed containers that are vertical and secure, Ensure that the people who transport the product know what to do in case of an accident or spill.

Overland transport

Classification code (ADR) : F1
 Special provisions (ADR) : 163, 367, 640C, 650
 Limited quantities (ADR) : 5I
 Excepted quantities (ADR) : E2
 Packing instructions (ADR) : P001
 Special packing provisions (ADR) : PP1
 Mixed packing provisions (ADR) : MP19
 Portable tank and bulk container instructions (ADR) : T4
 Portable tank and bulk container special provisions (ADR) : TP1, TP8, TP28
 Tank code (ADR) : L1.5BN
 Vehicle for tank carriage : FL
 Transport category (ADR) : 2
 Special provisions for carriage - Operation (ADR) : S2, S20
 Hazard identification number (Kemler No.) : 33
 Orange plates :



Tunnel restriction code (ADR) : D/E
 EAC code : •3YE

Transport by sea

Special provisions (IMDG) : 163, 367
 Limited quantities (IMDG) : 5 L
 Excepted quantities (IMDG) : E2
 Packing instructions (IMDG) : P001
 Special packing provisions (IMDG) : PP1
 IBC packing instructions (IMDG) : IBC02
 Tank instructions (IMDG) : T4
 Tank special provisions (IMDG) : TP1, TP8, TP28
 EmS-No. (Fire) : F-E
 EmS-No. (Spillage) : S-E
 Stowage category (IMDG) : B
 Properties and observations (IMDG) : Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA) : E2
 PCA Limited quantities (IATA) : Y341
 PCA limited quantity max net quantity (IATA) : 1L
 PCA packing instructions (IATA) : 353
 PCA max net quantity (IATA) : 5L
 CAO packing instructions (IATA) : 364
 CAO max net quantity (IATA) : 60L
 Special provisions (IATA) : A3, A72, A192

SC-7400

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Issue date: 12/11/2021 Revision date: 07/07/2022 Supersedes version of: 12/11/2021 Version: 1.1

ERG code (IATA)	: 3L
Inland waterway transport	
Classification code (ADN)	: F1
Special provisions (ADN)	: 163, 367, 640D, 650
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E2
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 1
Rail transport	
Classification code (RID)	: F1
Special provisions (RID)	: 163, 367, 640D, 650
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001, IBC02, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP8, TP28
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 2
Colis express (express parcels) (RID)	: CE7
Hazard identification number (RID)	: 33

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 25,9 % Definition according to EU Directive 2004/42/EC: All organic compounds with a boilingpoint of ≤ 250 °C at 101,3 kPa.

SC-7400

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
 Issue date: 12/11/2021 Revision date: 07/07/2022 Supersedes version of: 12/11/2021 Version: 1.1

Directive 2012/18/EU (SEVESO III)

Seveso Additional information : This product is controlled under Seveso Directive.

NAMED SUBSTANCES

Name: Propanone
 Notification and MAPP threshold: 2500t
 Safety report threshold: 25000t

DANGER CRITERIA

Category: C6: Flammable (R10)
 Notification and MAPP threshold: 5000t
 Safety report threshold: 50000t

Category: P5c: Flammable liquids 2 and 3 not falling under P5a or P5b
 Notification and MAPP threshold: 5000t
 Safety report threshold: 50000t

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
VOC	Volatile Organic Compounds
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
vPvB	Very Persistent and Very Bioaccumulative
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration

SC-7400

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Issue date: 12/11/2021 Revision date: 07/07/2022 Supersedes version of: 12/11/2021 Version: 1.1

PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
OEL	Occupational Exposure Limit
BLV	Biological limit value
TLM	Median Tolerance Limit
EC-No.	European Community number
CAS-No.	Chemical Abstract Service number
IARC	International Agency for Research on Cancer
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
ThOD	Theoretical oxygen demand (ThOD)
EN	European Standard
SDS	Safety Data Sheet
N.O.S.	Not Otherwise Specified
OECD	Organisation for Economic Co-operation and Development
STP	Sewage treatment plant
TRGS	Technical Rules for Hazardous Substances
IOELV	Indicative Occupational Exposure Limit Value
WGK	Water Hazard Class

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
EUH208	Contains . May produce an allergic reaction.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.



SC-7400

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Issue date: 12/11/2021 Revision date: 07/07/2022 Supersedes version of: 12/11/2021 Version: 1.1

H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Flam. Liq. 2	H225	Calculation method
Eye Irrit. 2	H319	Calculation method

SDS EU (REACH Annex II) STAHL

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.